Upright Laboratory Freezer

SP-FZ-25V270E

Capacity (L)	268
Size (W×D×H)(mm) / Internal	508×455×1137
Size (W×D×H)(mm) / External	673×676×1630
Temperature / Range (°C) at RT.10~32°C	-10 to -25
Temperature / Sensor	NTC
Temperature / Controller	Microprocessor
Cooling System / Refrigerant (CFC Free)	R290
Cooling System / Defrost	Manual
Cooling System / Compressor (Qty)	CUBIGELN/1
Display	Digital display
Audible & Visible Alarm / Standard	High/Low temperature, sensor error, door ajar
Audible & Visible Alarm / High Ambient Temperature	/
Audible & Visible Alarm / Abnormal Voltage	/
Audible & Visible Alarm / Power Failure Backup System (Alarm)	8h
Material / Internal	Electro-galvanized steel with antimicrobial powder coating
Material / E×ternal	Electro-galvanized steel with antimicrobial powder coating
Accessories / USB port	Optional
Accessories / Casters	Standard
Accessories / Data Logger	Optional
Accessories / Remote Alarm Port	Standard
Accessories / Test Hole (Qty) / Φ (mm)	1/25
Shelves / Drawers (Qty)	Shelves/3
Shelves / Drawers (Qty)	Shelves/3

Sound Emission (dB)	46
Electricity / Voltage / Frequency	AC 110/220V & Plusmn; 10%, 50/60Hz
Electricity / Consumption (W)	215
N.W./G.W. (kg)	98.5/115
Shipping Size (W×DxH) (mm)	770×770×1804