SCIENCE, PRECISION, INNOVATION

Vertical Pulse Vacuum Autoclave

SP-ST-V80PV

Capacity	80L
External Size (W×D×H)(mm)	636×710×1030
Chamber Size (Ø×H)(mm)	Ø386×695
Chamber Material	SUS304
Sterilization Temperature	105~136 ℃
Designed Temperature	150℃
Max. Working Temperature	136 ℃
Dissolution Temperature	40~100℃
Warming Temperature	40~60℃
Temp.Accuracy	0.1℃
Temp. Uniformity	≤±0.5℃
Designed Pressure	0.3Mpa
Max.Sterilization Pressure	0.23Mpa
Ultimate Vacuum	-0.096MPa
Pressure Resoluiton	0.1KPa
Sterilization Time Range	0~99min
Temp. Controller	PID control by microprocessor
Display	LCD touch screen
Drying Function	YES
Drying Time	15min
Sterilization Program	●Medical instrument program●Luminal instruments●Dressings/Fabric program●Rubber program●Liquid program●BD Test program●Vacuum Test progrmSterilization of medical dressing, medical Instruments, Instruments with cavity, Rubber, liquids plus 4 user-customized programs BD Test and vacuum test.
Water Injection Method	Built-in water tank
Power Consumption	4.5 kW
Power Supply	220V 50Hz

Standard SS Basket	2pcs
Net Weight	95kg
Gross Weight	130kg
Shipping Size (WD×H)(mm)	880×910×1300